ECONOLITE

Cabinets for Traffic Management

346LX Cabinets

The Safetran 346LX Series of traffic control cabinets are built to the exacting standards and specifications of NYDOT, Caltrans, FHWA, and TEES. Each 346LX cabinet feature a 19-inch EIA rack that provides ultimate ease and flexibility of traffic control component configuration.

The modular design of Econolite's Safetran 346LX cabinet provides control of up to eight vehicle and four pedestrian phases. The 346LX Series of cabinets also meet the stringent weatherproof requirements for State of California TEES enclosures.

Econolite's Safetran 346LX Series of traffic cabinets securely houses the signal controller and other vital intersection electronic equipment that manages efficient intersection operations and traffic flow. The strict adherence to industry standards and specifications ensures the highest levels of safety for all roadway users.



Key Features

- Protects technicians from accidental contact with high voltages
- Interchange standard assemblies and components easily through modular design
- Access spacious cabinet interior easily through double doors, front and back
- Secure cabinet with threepoint latching system and industry standard locks



Safetran Traffic Cabinets by Econolite



Description

The Safetran 346LX Cabinet is the newest in the line of Caltrans fully functional traffic controller cabinets that have put the customer and users' needs at the forefront. After many years of being exposed to dangerous voltages inside of traffic control cabinets, Caltrans has answered the need to comply with stringent safety standards of the NEC (National Electrical Code) and OSHA (Occupational Safety and Health Act). As part of the new 2009 Caltrans Electrical Equipment Specification incorporating Errata 2 Caltrans has also taken into consideration the many additional uses that the modern traffic controller cabinet can be used for by enlarging the cabinet housing design to be able to accommodate the most advanced intersection management applications. These applications, CCTV management, Sign Controls, Data Management, Fiber and Communication hubs and more are all easily added to this new cabinet design.

Benefits


- Strict safety standards to protect traffic technician personnel from exposure to high voltages when working in the traffic controller environment
- Standardized cabinet housing design for multi-purpose uses
- Modularized assemblies that are interchangeable and field
 replaceable
- Customer specified options are available when needed
- 4 door cabinet design for maximum accessibility to all cabinet functionality
- Completely customizable to intersection needs


Basic Specifications


- Dimensions
 - 50.5 in. H x 44.2 in. W x 26 in. D
- Material
 - Aluminum 0.125 in. (painted inside/outside)
- Ship Weight
 - 360 lbs (with no plug-ins or controller)

Features

- 8-phase, 4-pedestrian operation (or 2-pedestrian, 2-overlap) (1-Output file)
- 18 detector channel capability
 (3-left turn, 6-through movement) (1-Input file)
- 2/4 detector channel modules (plug ins specify)
- · 2-railroad, 4-evp inputs available
- Solid State signal bus relay (SSR) with Fault Indicator light (no mercury contactor available)
- 24VDC control to the load switches, backup protection if SSR fails
- Red/Yellow programmable flash via molex flash plugs
- DC isolator for input file interfacing to ped push buttons
 or special functions
- Conflict Monitor Unit slot for series 210 or 2010 CMU.
- Transient Voltage and surge suppression filter
- Drawer/shelf combo
- C11 harness
- Fluorescent or LED light assemblies available.







ECONOLITE

1250 N. Tustin Avenue, Anaheim, CA 92807

/14-630-3700

sales@econoli[,]

www.econolite.com

SFTR.346LX 05-21.1

© 2021 Econolite. All rights reserved. Econolite reserves the right to change or update these specifications at any time without prior notification